



LTE3316-M604

4G LTE-A Indoor IAD

The Zyxel LTE3316-M604 4G LTE-A Indoor IAD supports Cat. 6 integrated voice router with AC1200 dual-band concurrent links. Users can enjoy lightning-fast mobile Internet connectivity with data rates of up to 300/50 Mbps (downlink/uplink) and it's backward compatible with 4G and 3G network connections. Besides, the multi-WAN design provides users with a fail-safe, consistent and reliable broadband Internet access via either mobile WAN or fixed-line WAN configurations.

With plug-and-play, responsive Web GUI wizard and "Zyxel Air app" features, the Zyxel LTE3316 offers an enjoyable, easy-to-use and simple router management experience through a smart phone or a tablet.

The Zyxel LTE3316 is designed for operators to offer end-users with better Internet experience taking advantage of reliable Internet connection, lightning-fast internet connectivity, lag-free online video and music streaming as well as high-quality voice calls at home, in the office or remote area within mobile Internet coverage without wire limitations.



Lightning-fast mobile Internet with data rates of up to 300/50 Mbps (DL/UL)



AC1200 dual-band concurrent links



CS-Voice



Bridge and Router modes



Mobile WAN with failover to Ethernet WAN



External LTE/3G antenna ports (SMA-female)




Zyxel Air app for iOS or Android**

Benefits


Lightning-fast mobile Internet connectivity

The Zyxel LTE3316 4G LTE-A Indoor IAD provides lightning-fast mobile Internet access twice faster than UE Cat. 4 and is better than fixed-line Ethernet connectivity. It also supports 4G LTE-A 2x DL Carrier Aggregation with download data rates of up to 300 and uplink speeds of up to 50 Mbps, and it's backward compatible with 4G and 3G broadband networks.



Bridge and Router modes

With bridge and router modes embedded, the Zyxel LTE3316 is adaptive to most Ethernet devices and gateways for seamless integration with your current CPE in a very simple yet complete way to meet user needs.




Enjoy WiFi sharing with AC1200 dual-band concurrent wireless LAN

The super-fast WiFi built into Zyxel LTE3316 has data speeds of up to 1200 Mbp with 802.11n and 802.11ac dual-band (2.4 GHz and 5 GHz) concurrent wireless LAN. Users can enjoy WiFi sharing with ideal coverage with up to 32 devices connected simultaneously.



Multi-WAN failover for non-stop Internet connection

The Multiple-WAN design provides consistent fail-safe Internet connection, with which users can stay connected via the Mobile WAN or Ethernet WAN.



Ultra-high quality voice calls

Integrated voice support allows users to enjoy making ultra-high quality CSFB calls.



Specifications

System Specifications

IP Networking

- Cellular and Ethernet WAN failover and failback
- Support IPv4
- DHCP server/client
- ICMP supported (LAN and/or WAN, disable)
- Multiple APNs**
- Data roaming disable/enable
- IP firewall
- NAT/NAPT
- Port forwarding DMZ
- DNS, DDNS
- Support NAT Router mode
- Support Bridge mode (IP pass-through)

Wireless Feature

- Auto channel selection
- WiFi Protected Setup (WPS)
- WiFi Multimedia (WMM) QoS
- Support None, WPA2-PSK
- MAC address filtering with 32 address supported
- Multiple SSIDs/Hide SSIDs
- Up to 32 WiFi clients

Voice Service

- CS-Voice:
 - Standard compliant: 3GPP TS 23.272 Release 9
 - Support CSFB from LTE to 3G

Management

- APN management
- SIM PIN/PUK management
- SMS management (send and receive message)
- Secure remote management via TR-069/WebGUI
- Over-the-Air (OTA) firmware upgrade: TR-069/WebGUI
- Network selection
- Operating frequency band selection
- Setup Wizard
- Store configuration
- Zyxel Air app for iOS or Android**

Hardware Specifications

LTE Air Interface

- Standard compliant: 3GPP Release 10 Cat. 6
- Support LTE band: 1/3/5/7/8/20/28/32/38/40/41

- Supported frequency:
 - LTE FDD 2600/2100/1800/900/850/800/700MHz
 - LTE TDD 2600/2500/2300 MHz
- 2 Carrier Aggregation combination: B1+B1/B5/B8/B20/B28 B3+B3/B5/B7/B8/B20/B28 B7+B5/B7/B8/B20/B28 B38+B38; B40+B40; B41+B41
- LTE antenna: 2 internal antennas
- Peak data rate:
 - 300 Mbps DL within 40 MHz bandwidth (CA)
 - 50 Mbps UL within 20 MHz bandwidth

UMTS/GSM Air Interface

- Standard compliant: WCDMA band 1/3/5/8
- Supported frequency:
 - HSPA+/UMTS 2100/1800/900/850 MHz (Band 1/3/5/8)
 - WCDMA: 2100/1800/900/850 MHz
 - HSPA+ downlink data rate up to 42 Mbps
 - HSUPA uplink data rate up to 5.76 Mbps

WiFi Air Interface

- Wireless standard (Concurrent):
 - IEEE 802.11 b/g/n, 2.4 GHz
 - IEEE 802.11 a/n/ac, 5 GHz
- Wireless link speed:
 - 300 Mbps* for 2.4 GHz
 - 867 Mbps* for 5 GHz
- WiFi 2.4 GHz antenna: 2x2 internal antennas up to 3 dBi
- WiFi 5 GHz antenna: 2x2 internal antennas up to 5 dBi

Hardware Interface

- Four GbE RJ-45 LAN ports. LAN1 can be configured as Ethernet WAN port
- LEDs:
 - Power indication
 - Internet status
 - LTE/3G signal strength
 - WiFi status
 - FXS status
- One WPS & WiFi on/off button
- One 3FF micro SIM card socket
- One reset to default button
- One power on/off button
- One DC power jack
- One FXS RJ-11 phone port
- Two external LTE/3G antenna SMA connector (for external antenna option)

Power Specifications

- Power consumption: 13 Watt (peak)
- External power supply: 110 - 240 V AC/12 V DC adaptor

Physical Specifications

- Dimensions (WxDxH): 202 x 157 x 35 mm (7.95" x 6.18" x 1.37")
- Weight: 400 g (0.88 lb.)

Environmental Specifications

Operating Environment

- Temperature: 0°C to 40°C (32°F to 140°F)
- Humidity: 10% to 90% RH (Non-condensing)

Storage Environment

- Temperature: -40°C to 70°C (-40°F to 158°F)
- Humidity: 0% to 95% RH (Non-condensing)

Certification

- CE

Package Contents

- Power adapter
- Ethernet cable
- Quick start guide
- Warranty card
- CE DoC
- Safety warning

* The maximum wireless data transfer rate is derived from IEEE Standard 802.11 specifications. Actual data transfer rate will vary from network environment including: distance, network traffic, building site materials/construction, interference from other wireless devices, and other adverse conditions.


** Under development.

Zyxel Air App




Application Diagram

Application 1



Application 2



For more product information, visit us on the web at www.zyxel.com

Copyright © 2021 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.



20/12/21