

CVT-3512 Series Media Converter



10/100/1000BASE-T to 1000BASE-X Stand-alone Managed Media Converter with 802.3ah OAM Compliance

Features

- **The World-wide smallest OAM Managed Media Converter**
The smallest media converter with SNMP and IEEE 802.3ah OAM managed solution in the world-wide
- **9K Bytes Jumbo Frame Size**
Support jumbo frame size 9K bytes to ease the network traffic loading and facilitate IPTV service
- **Selectable ISP Ethernet Tag Type**
With selectable ISP Ethernet Tag Type, the service providers can transport the encapsulated traffic for different customers without security risk
- **Power Down Trap**
The media converter can concurrently deliver popular SNMP trap message and OAM dying gasp to rapidly identify network fault due to power outage and reduce track rolls to save OPEX for operators and service providers
- **Fully Compatible with CVT-RACK-16**
Budget limited solution for CVT-Rack-16 to mix installation with CTS's Non-managed converter

Target Applications

- **Managed media converter which required IEEE 802.3ah OAM to monitor point-to-point connection for the deployment of FTTX applications**


Description

Connection Technology Systems (CTS) CVT-3512 series are Gigabit Ethernet 10/100/1000Base-T to 1000Base-X media converter which is designed to fulfill the emerging deployment needs of fiber Ethernet network for operators and service providers with SNMP and IEEE802.3ah OAM managed functionality. When CVT-3512 is deployed at customer premises, the media converter can be fully managed by the network equipment in the Central Office site which support IEEE 802.3ah OAM standard as well. By leveraging the benefits of IEEE802.3ah OAM, the CVT-3512 media converter is a cost effectively solution to save capital expenditure (CAPEX) and enhance the reliability of point-to-point connection as well as offer the robust fault managed capability to significantly reduce the operational expenditure (OPEX) for operators and service providers.

The CVT-3512 series media converter allow the user to connect Ethernet twisted-pair network to fiber Ethernet network easily and extend the transmission distance from 10Km to 80Km maximized. The optical interface of media converter provides a wide range of options to fit the practically need of fiber network deployment for the customer included multi-mode, single-mode and bi-directional transmission over just one single fiber as well as the SFP slot for pluggable fiber transceiver.

The CVT-3512 series media converter is fully compliant with IEEE802.3/802.3u/802.3ab & 802.3z standards. The installation and operation procedures for CVT-3512 are quite simple and straight forward. The user can simply configure the built in popular layer 2 and managed features by using commonly Web management UI to monitor the operation status easily in real time.

Application Diagram



Specification

Interface

TP port
10/100/1000Base-T RJ45 x 1
F/O port
1000Base-X x 1

Standards

IEEE 802.3 10Base-T
IEEE 802.3u 100Base-TX/FX
IEEE 802.3ab 1000Base-T
IEEE 802.3z 1000Base-X
IEEE 802.3x flow control
IEEE 802.3ah EFM

H/W Specification

Store and forward switching mechanism
Auto-Cross over for MDI/MDI-X in TP port
Auto-Negotiation in TP port
Full/Half duplex mode operation
1K MAC address table
32K bytes memory buffer
Link alarm

LED

Power, FDX, Status, Speed,
F/O Link/Act, TX Link/Act

Ethernet Features

Support 9K bytes jumbo frame
Support flow control
IEEE 802.1Q tag VLAN
Q-in-Q VLAN configuration
Selectable ISP Ethernet tag type
Bandwidth control

Network Management

Web UI management
- SNMP management
- Support SNMP v1/v2c
- Support DHCP client
- Support private, RFC-1213, RMON
(group 1, 2, 3, 9) MIBs
- HTTP firmware upgrade
- Support power down trap
- SFF-8472 diagnostic monitoring
interface (CVT-3512SFP only)

Power Requirement

Power adaptor
- AC input: 100VAC~240VAC
- Frequency range: 50~60Hz
- DC output: 5V, 1A
Power consumption: 3.4W

Environmental Condition

Operation: 0° ~ 50°C
Storage temperature: -20° ~ 60°C
Humidity: 5% ~ 90% non-condensing

Dimension & Weight

Size: 71 x 94 x 26 mm (WxDxH)
Shipping weight: 0.6kg

EMC/Safety

FCC class A,
CE
* For further reports, please contact us for
update

Order Information

MODEL	FIBER PORT					TP PORT	
	Speed	Fiber Type	Connector	Distance	Ports	Speed	Ports
CVT-3512BTFC	1000	MM	SC	550M	1	10/100/1000	1
CVT-3512BTFC(SM-10/20/30/50/80)	1000	SM	SC	10/20/30/50/80KM	1	10/100/1000	1
CVT-3512W2A(SM-10/20/40)	1000	WDM	SC	10/20/40KM	1	10/100/1000	1
CVT-3512W2B(SM-10/20/40)	1000	WDM	SC	10/20/40KM	1	10/100/1000	1
CVT-3512SFP	1000	SFP	-	-	1	10/100/1000	1

SFP-31 Series

MODEL	FIBER PORT				
	Speed	Type	Connector	Distance	Wavelength
SFP-31FC	1000Mbps	MM	LC	550M	850nm
SFP-31FC(SM-10/20/40/50/80/120)	1000Mbps	SM	LC	10/20/40/50/80/120KM	1310nm/1310nm/1310nm/1550nm/1550nm/1550nm
SFP-31W2A(SM-10/20/40/80)	1000Mbps	WDM	LC	10/20/40/80KM	TX:1310nm/1310nm/1310nm/1490nm
					RX:1550nm/1550nm/1550nm/1570nm
SFP-31W2B(SM-10/20/40/80)	1000Mbps	WDM	LC	10/20/40/80KM	TX:1550nm/1550nm/1550nm/1570nm
					RX:1310nm/1310nm/1310nm/1490nm
SFP-31FC-C09	1000Mbps	CWDM	LC	80KM	1430nm
SFP-31FC-C10	1000Mbps	CWDM	LC	80KM	1450nm
SFP-31FC-C11	1000Mbps	CWDM	LC	80KM	1470nm
SFP-31FC-C12	1000Mbps	CWDM	LC	80KM	1490nm
SFP-31FC-C13	1000Mbps	CWDM	LC	80KM	1510nm
SFP-31FC-C14	1000Mbps	CWDM	LC	80KM	1530nm
SFP-31FC-C15	1000Mbps	CWDM	LC	80KM	1550nm
SFP-31FC-C16	1000Mbps	CWDM	LC	80KM	1570nm
SFP-31FC-C17	1000Mbps	CWDM	LC	80KM	1590nm
SFP-31FC-C18	1000Mbps	CWDM	LC	80KM	1610nm